SAFETY DATA SHEET



This Safety Data Sheet (SDS) complies with the requirements of the U.S. Federal Occupational Safety and Health Administration Hazard Communication Standard (29 CFR 1910.1200, as updated in 2012) and equivalent state Standards. It has also been developed in accordance with the United Nations Globally Harmonized System of Classification of Chemicals (GHS) and the Canadian Workplace Hazardous Materials Information System (WHMIS). Refer to Section 16 of this document for the definition of terms and abbreviations.

SECTION 1: IDENTIFICATION

1.1 PRODUCT IDENTIFIER

ITEM NUMBER(S): 160271
 ZEP NUMBER: A00238BP

PRODUCT NAME: Country Day Dry Deodorizer and Odor Counteractant

1.2 RELEVANT IDENTIFIED USES OF THE MIXTURE

RECOMMENDED USE: Room deodorizer.

• IDENTIFIED USERS: For sale to, use and storage by service persons only.

1.3 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

MANUFACTURER/

SUPPLIER: WAXIE Sanitary Supply

ADDRESS: 9353 Waxie Way; San Diego, CA 92123-1036

BUSINESS PHONE: 1-800-995-4466

• EMERGENCY PHONE: 1-800-255-3924 (CHEMTEL; 24 hours)

1.4 OTHER PERTINENT INFORMATION

 This product is sold and used in relatively small volumes. This SDS has been developed to address safety concerns affecting small volume handling situations and those involving warehouses and workplaces where large numbers of these items are stored or distributed.

SECTION 2: HAZARD IDENTIFICATION

2.1 EMERGENCY OVERVIEW

Appearance	Aerosol containing a liquefied gas		
Color	Colorless		
Odor	Odorized		

2.2 GHS CLASSIFICATION OF THE SUBSTANCE OR MIXTURE

OSHA/HCS Status

Classification of the Substance or Mixture:

Flammable aerosols (Category 1); Gases under pressure (Liquefied gas); Eye irritation (Category 2A); Skin sensitization (Category 1); Specific target organ toxicity - single exposure (Category 3, Central nervous system).

2.3 LABEL ELEMENTS (suggested)

Hazard Pictograms:







Signal Word: Danger.

Hazard Statements: Extremely flammable aerosol. Contains gas under pressure; may explode if

heated. May cause allergic skin reaction. Causes serious eye irritation. May cause

dizziness or drowsiness.

SECTION 2: HAZARD IDENTIFICATION (Continued)

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas/ mist/ vapors/ spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear eye

protection/ face protection. Wear protective gloves.

Response: IF ON SKIN: Wash with plenty of soap and water. IF INHALED: Remove victim to fresh

air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/ attention. If eye irritation persists: Get

medical advice/ attention. Wash contaminated clothing before reuse.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect

from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal: Dispose of contents/container in accordance with local regulation.

2.4 OTHER PERTINENT HAZARDS NOT OTHERWISE CLASSIFIED

· Carcinogenicity:

our onloge	our onlogomony.			
IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.			
ACGIH	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH.			
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by OSHA.			
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by NTP.			

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

3.1 **SUBSTANCES/MIXTURES**

Hazardous Components:

CHEMICAL	CAS NUMBER	% (v/v)
Acetone	67-64-1	>= 70 - < 90
Propane	74-98-6	>= 10 - < 20
Butane	106-97-8	>= 5 - < 10
Coumarin	91-64-5	>= 0.1 - < 1
2-Phenylethanol	60-12-8	>= 0.1 - < 1
Benzyl Salicylate	118-58-1	>= 0.1 - < 1

SECTION 4: FIRST AID MEASURES

4.1 DESCRIPTION OF FIRST AID MEASURES

General advice: Move out of dangerous area. Show this safety data sheet to the doctor in

attendance. Do not leave the victim unattended.

If inhaled: Consult a physician after significant exposure. If unconscious place in recovery

position and seek medical advice.

In case of skin contact: If skin irritation persists, call a physician. Wash off immediately with plenty of

water for at least 15 minutes. If on clothes, remove clothes.

In case of eye contact: Remove contact lenses. Protect unharmed eye. Keep eye wide open while

rinsing. If eye irritation persists, consult a specialist. If in eyes, rinse with water for

15 minutes.

If swallowed: DO NOT induce vomiting unless directed to do so by a physician or poison control

center. Keep respiratory tract clear. Obtain medical attention. Never give anything by mouth to an unconscious person. Take victim immediately to

hospital.

SECTION 5: FIREFIGHTING MEASURES

5.1 **DESCRIPTION OF FIREFIGHTING MEASURES**

Suitable extinguishing media: Alcohol-resistant foam

> Dry chemical Carbon dioxide (C02) Water spray jet

Unsuitable extinguishing

media:

High volume water jet

Specific hazards during

firefighting:

Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion

product:

Carbon dioxide (CO2). Carbon monoxide. Smoke.

Specific extinguishing

methods:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information: For safety reasons in case of fire, cans should be stored separately in closed

containments. Use a water spray to cool fully closed containers.

Special protective equipment

for firefiahters:

Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES

Personal precautions, protective equipment and emergency procedures:

Use personal protective equipment. Ensure adequate ventilation.

Remove all sources of ignition. Evacuate personnel to safe areas.

Beware of vapors accumulating to form explosive concentrations. Vapors can

accumulate in low areas.

Environmental precautions: Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform respective

authorities.

Methods and materials for

containment and cleaning up:

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal

binder, sawdust).

Sweep up and shovel into suitable containers for disposal.

SECTION 7: HANDLING AND STORAGE

7.1 PRECAUTIONS FOR SAFE HANDLING AND STORAGE

Advice on safe handling: Always replace cap after use. Do not breathe vapors or spray mist. Avoid

> contact with skin and eyes. Take precautionary measures against static discharges. Use only with adequate ventilation. Provide sufficient air exchange and/or exhaust in work rooms. Dispose of rinse water in accordance with local

and national regulations.

Conditions for safe storage: BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and

temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. No smoking. Observe label precautions. Keep in a cool, dry, well-ventilated place. Electrical installations /

working materials must comply with the technological safety standards.

Materials to avoid: Oxidizing agents. Store and keep away from bases and alkalis.

Storage temperature: < 54.4 °C

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 CONTROL PARAMETERS

AIRBORNE EXPOSURE LIMITS:

COMPONENT	ACGIH TLV	OSHA PEL	NIOSH REL	OTHER
Acetone	TWA = 500 ppm; STEL = 750 ppm	TWA = 1000 ppm	TWA = 250 ppm	NE
Propane	Minimal Oxygen Content (19.5% at Sea Level)	TWA = 1000 ppm	TWA = 1000 ppm	NE
Butane	STEL = 1000 ppm	NE	TWA = 800 ppm	NE

- BIOLOGICAL OCCUPATIONAL EXPOSURE LIMITS: The following BEIs have been established for components of this product.
 - Acetone (with Hydrolysis): Acetone in Urine; End of Shift; 25 mg/L

8.2 EXPOSURE CONTROLS AND PERSONAL PROTECTION

Respiratory protection: Use respiratory protection unless adequate local exhaust ventilation is

provided or exposure assessment demonstrates that exposures are within

recommended exposure guidelines.

Hand protection: The suitability for a specific workplace should be discussed with the producers

of the protective gloves.

Eye protection: Safety glasses. Ensure that eyewash stations and safety showers are close to

the workstation location.

Skin and body protection: Impervious clothing. Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures: When using do not eat or drink. When using do not smoke. Wash hands

before breaks and at the end of workday.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Aerosol containing a liquefied gas.

Color:Colorless.Odor:Odorized

Odor Threshold:

PH:

Not applicable.

Melting point/freezing point:

Boiling point:

Flash point:

Evaporation rate:

No data available.

No data available.

Not applicable.

Not applicable.

No data available.

Flammability (solid, gas): Extremely flammable aerosol.

Upper explosion limit:

Lower explosion limit:

Vapor pressure:

Relative vapor density:

No data available.

No data available.

No data available.

No data available.

O.795 g/cm3

Solubility(ies)/Water solubility:

Solubility in other solvents:

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Thermal decomposition:

Viscosity - Viscosity, kinematic:

Heat of combustion:

Completely soluble.

No data available.

No data available.

No data available.

No data available.

34.86 kJ/g.

SECTION 10: STABILITY AND REACTIVITY

10.1 REACTIVITY, STABILITY, AND CONDITIONS TO AVOID

Reactivity: Stable.

Chemical stability: Stable under normal conditions.

Possibility of hazardous Vapors may form explosive mixture with air. No decomposition if stored

and applied as directed.

reactions:

Conditions to avoid:

Heat, flames and sparks. Extremes of temperature and direct sunlight.

Incompatible materials: Oxidizing agents; Bases; Amines.

Hazardous decomposition Carbon dioxide (CO2); Carbon monoxide.

products:

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 <u>INFORMATION ON ACUTE EFFECTS</u>

PRODUCT

Acute oral toxicity: Acute toxicity estimate : > 5,000 mg/kg; Method: Calculation method Acute dermal toxicity: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method

COMPONENTS

Acetone

Acute oral toxicity:

Acute inhalation toxicity:

LD50 rat: 5,800 mg/kg

LC50 rat: 132 mg/l

Exposure time: 3 h

LC50 rat: 50.1 mg/l

Acute dermal toxicity: LD50 guinea pig: > 7,426 mg/kg

LD50 rabbit: > 7,426 mg/kg

Propane

Acute inhalation toxicity LC50 mouse: 1,237 mg/l

Exposure time: 2 h LC50 rat: 658 mg/l Exposure time: 4 h LC50 rat: 1,355 mg/l

Butane

Acute inhalation toxicity LC50 mouse: 1,237 mg/l

Exposure time: 2 h LC50 rat: 1,355 mg/l

Coumarin

Acute oral toxicity: LD50 Oral rat: 293 mg/kg

2-Phenylethanol

Acute oral toxicity: LD50 Oral rat: 1,790 mg/kg
Acute dermal toxicity: LD50 Oral rabbit: 806 mg/kg

Benzyl Salicylate

Acute oral toxicity: LD50 Oral rat: 2,227 mg/kg

11.2 <u>INFORMATION ON OTHER HEALTH EFFECTS</u>

PRODUCT

Skin corrosion/Irritation: Remarks: Slight irritating.

Serious eye damage/eye

irritation:

Remarks: Irritating to eyes.

Respiratory or skin

sensitization:

Causes skin sensitization.

SECTION 11: TOXICOLOGICAL INFORMATION (Continued)

COMPONENTS

Germ cell mutagenicity:

Carcinogenicity:

Reproductive toxicity:

STOT - single exposure:

STOT - repeated exposure

Aspiration toxicity:

No data available.

No data available.

No data available.

No data available.

FURTHER INFORMATION Remarks: Symptoms of overexposure may be headache, dizziness,

tiredness, nausea and vomiting. Concentrations substantially above the TLV value may cause narcotic effects. Solvents may degrease the skin.

SECTION 12: ECOLOGICAL INFORMATION

12.1 TOXICITY INFORMATION

Ecotoxicity:Persistence and degradability:
No data available.
No data available.

Bioaccumulative potential – PRODUCT: Partition coefficient: n-octanol/water No data available

Bioaccumulative potential – BUTANE: Partition coefficient: n-octanol/water Pow: 2.89 **Bioaccumulative potential – 2-PHENYL-** Partition coefficient: n-octanol/water Pow1.36

ETHANOL:

Mobility in soil:No data available.Other adverse effects:No data available.

12.2 OTHER PRODUCT INFORMATION

REGULATION: 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA

Section 602 Class I Substances

Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as

defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information: No data available.

SECTION 13: DISPOSAL CONSIDERATION

13.1 WASTE TREATMENT METHODS

- Dispose of in accordance with local, State and Federal regulations.
- Dispose of unused product properly. Do not re-use empty containers.

13.2 DISPOSAL CONSIDERATIONS

EPA RCRA WASTE CODE: D001.

SECTION 14: TRANSPORT INFORMATION

14.1 DANGEROUS GOODS BASIC DESCRIPTION AND OTHER TRANSPORT INFORMATION

• DEPARTMENT OF TRANSPORTATION HAZARDOUS MATERIALS SHIPPING REGULATIONS:

ORM-D, CONSUMER COMMODITY

• CANADIAN TRANSPORTATION INFORMATION: This product is regulated by Transport Canada as dangerous goods under Canadian transportation standards. Use the following information:

UN 1950, Aerosols, Flammable, 2.1 (Limited Quantity)

• **IATA DESIGNATION**: This product is regulated as dangerous goods by the International Air Transport Association. Use the following information:

UN 1950, Aerosols, Flammable, 2.1 (Limited Quantity)

• **IMDG DESIGNATION**: This product is regulated as dangerous goods by the International Maritime Organization. Use the following information:

UN 1950, Aerosols, Flammable, 2.1 (Limited Quantity)

SECTION 15: REGULATORY INFORMATION

15.1 UNITED STATES REGULATIONS

- EPCRA Emergency Planning and Community Right-to-Know Act
- CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Acetone	67-64-1	5000	*

^{*}Calculated RQ exceeds reasonably attainable upper limit.

- SARA 304 Extremely Hazardous Substances Reportable Quantity: This material does not contain any components with a section 304 EHS RQ.
- Other Important Regulations:

SARA 311/312 Hazards: Fire Hazard

Sudden Release of Pressure Hazard

Acute Health Hazard

SARA 302: SARA 302: No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.

SARA 313: SARA 313: This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels

established by SARA Title III, Section 313.

California Prop 65:

Product contains amounts of the WARNING! This product contains a

following items below GHS reporting chemical known to the State of

limits: California to cause cancer.

Benzophenone-119-61-9

15.2 OTHER REGULATIONS

TSCA On TSCA Inventory

DSL This product contains one or several components that are not on

the Canadian DSL nor NDSL.

AICS
Not in compliance with the inventory.

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16: OTHER INFORMATION

16.1 <u>INDICATION OF CHANGE</u>

DATE OF REVISION: December 10, 2015

• **SUPERCEDES**: May 18, 2015

CHANGE INDICATED: Format alterations.

16.2 KEY LITERATURE REFERENCES AND SOURCES FOR DATA

SAFETY DATA SHEET FOR MANUFACTURER PRODUCT.

2*

4

2 B

16.3 HAZARDOUS MATERIALS CLASSIFICATION SYSTEM

Health
Flammability
Physical Hazard

* Skin Senzitization

Physical Hazard
Protective

<u>HMIS Personal Protective Equipment Rating</u>: Occupational Use situations: B - Safety glasses and gloves.

16.4 PERSONAL PROTECTION SYMBOLS

Hand Protection



Eye Protection



16.5 NFPA INFORMATION

Equipment

NFPA Rating



NFPA Classification

Extremely Flammable Aerosol

16.6 DISCLAIMER

WAXIE Sanitary Supply makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of their own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by WAXIE Sanitary Supply as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does WAXIE Sanitary Supply assume any liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process. WAXIE Sanitary Supply does not recommend blending this product with any other chemicals. All information, recommendations and data contained herein concerning this product are based upon information available at the time of writing from recognized technical sources.

SECTION 16: OTHER INFORMATION (Continued)

16.7 ABBREVIATIONS AND ACRONYMS

ALL SECTIONS: OSHA: U.S. Federal Occupational Safety and Health Administration. WHMIS: Canadian Workplace Hazardous Materials Standard. GHS: Globally Harmonized System of Classification of Chemical Substances. REACH: European Union regulation, Registration, Evaluation, Authorization and Restriction of Chemical substances.

SECTION 2: <u>CAS Number</u>: Chemical Abstract Service Number, which is used by the American chemical Society to uniquely identify a chemical.

SECTION 8: NE: Not established. ACGIH: American Conference of Government Industrial Hygienists; TWA: Time-Weighted Average (over an 8-hour work day); STEL: Short-Term Exposure Limit (15 minute average, no more than 4-times daily and each exposure separated by one-hour minimally); C: Ceiling Limit (concentration not to be exceeded in a work environment). PEL: Permissible Exposure Limit. NIOSH: National Institute of Occupational Safety and Health; REL: Recommended Exposure Limit; IDLH: Immediately Dangerous to Life and Health Concentrations. Note: In July 1992, a court rulling vacated the more protective PELs set by OSHA in 1989. Because OSHA may enforce the more protective levels under the "general duty clause", both the current and vacated levels are presented in this document. ppm: Parts per Million. mg/m²: Milligrams per cubic meter. mppcf: Millions of Particles per Cubic Foot. BEL: Biological Exposure Limit. EL: Exposure Limit (United Kingdom). Federal Republic of Germany (DFG) Maximum Concentration Values in the Workplace (MAKs)

SECTION 9: <u>pH</u>: Scale (0 to 14) used to rate the acidity or alkalinity of aqueous solutions. For example, a pH value of 0 indicates a strongly acidic solution, pH of 7 indicates a neutral solution, and a pH value of 14 indicates an extremely basic solution. <u>FLASH POINT</u>: Temperature at which a liquid generates enough flammable vapors so that ignition may occur. <u>AUTOIGNITION TEMPERATURE</u>: Temperature at which spontaneous ignition occurs.

SECTION 9 (Continued): LOWER EXPLOSIVE LIMIT (LEL): The minimal concentration of flammable vapors in air which will sustain ignition. <u>UPPER EXPLOSIVE LIMIT (UEL)</u>: The maximum concentration of flammable vapors in air which will sustain ignition.≈: Approximately symbol. <u>VOC</u>: Volatile Organic Compound.

SECTION 11: CARCINOGENICITY STATUS: NTP: National Toxicology Program. IARC: International Agency for Research on Cancer. REPRODUCTIVE TOXICITY INFORMATION: Mutagen: Substance capable of causing chromosomal damage to cells. Embryotoxin: Substance capable of damaging the developing embryo in an overexposed female. Teratogen: Substance capable of damaging the developing fetus in an overexposed female. Reproductive toxin: Substance capable of adversely affecting male or female reproductive organs or functions. TOXICOLOGY DATA: LDxxor LCxx: The Lethal Dose or Lethal Concentration of a substance which will be fatal to a given percentage (xx) of exposed test animals by the designate route of administration. This value is used to access the toxicity of chemical substances to humans. TDxxor TCxx: The Toxic Dose or Toxic Concentration of a substance which will cause an adverse effect to a given percentage (xx) of exposed test animals by the designate route of administration.

SECTION 12: EC50: Effect Concentration (on 50% of study group); BOD: Biological Oxygen Demand. N/LOEC: No/Lowest Observable Effect Concentration.

SECTION 13: <u>RCRA</u>: Resource Conservation and Recovery Act. The regulations promulgated under this act under Act are found in 40 CFR, Sections 260 ff, and define the requirements of hazardous waste generation, transport, treatment, storage, and disposal. <u>EPA RCRA Waste Codes</u>: Defined in 40 CFR Section 261.

SECTION 15: CERCLA: Comprehensive Environmental Response Compensation and Liability Act (a.k.a. "Superfund") and SARA: (Superfund Amendment and Reauthorization Act). The regulations promulgated under this Act are located under 40 CFR 300 ff. and provide "community right-to-know" requirements. TSCA: Toxic Substances Control Act: Rules regulating the manufacture and sale of chemicals found in 40 CFR 700-766. DSL/NDSL: Canadian Domestic Substances and Non-Domestic Substances Lists.

SECTION 16: <u>HAZARDOUS MATERIALS IDENTIFICATION SYSTEM RATING</u>: This is a rating system used by industry to summarize physical and health hazards to chemical users and was originally developed by the National Paint and Coating Association. 0 = No Significant Hazard. 1 = Slight Hazard. 2 = Moderate Hazard. 3 = Severe Hazard. 4 = Extreme Hazard.